# Tumaker
# MODULAR PRINTERS

DATASHEET



One extruder



Independent double extruder



Independent double extruder

| | Mini Modular | NX Modular | BigFoot Modular |
|---|---|---|---|
| Printing volumen | 200 x 200 x 200 mm | 300 x 300 x 250 mm | 500 x 500 x 500 mm |
| Printer weight | 17 kg | 60kg | 92kg |
| Printer size | 414 x 481 x 500 mm | 840 x 635 x 805 mm | 1040 x 835 x 1044 mm |
| Package weight | 48 kg | 114kg | 160kg |
| Package weight | 729 x 533 x 709 mm | 953 x 800 x 957 mm | 1153 x 1000 x 1197 mm |
| Max. power | 1000 W | 1000 W | 1750 W |



Heated bed 100 °C

Extruder temperature 300 °C

**Heated chamber (only on Mini Modular)**

Closed structure with filters

Noise level: 44 dB
Closed door: 40 dB





**Connectivity**
Ethernet
Wi-Fi

Display: 5" - 7" Colour touch screen

Control browser:
MacOS, Windows, Linux
**Chrome, Edge, Safari, etc.**



SIMPLIFY3D

Simplify3D Software

Files: STL, OBJ, AMF

Compatible with other Slicers

**+Info**

Intelligent Energy Management
Automatic build plate leveling
MicroSD storage
1 Year warranty



# Tumaker
# INTERCHANGEABLE EXTRUDERS



## Filament
1.75 mm

Nozzles**:

- 0.15 mm
- 0.25 mm
- 0.4 mm
  Included with the extruder
- 0.6 mm
- 0.8 mm

## Pellet

Nozzles**:

- 0.4 mm
- 0.6 mm
- 0.8 mm
  Included with the extruder
- 2.0 mm
- 4.0 mm
- 5.0 mm

Optimised materials:

- ABS
- ASA
- NYLON
- PET-G
- PLA
- PP
- TPU Hardness
- TPU

Pellet recommended size:

- Circular of 3 mm - 5 mm**

Up to 6kg spools
Direct drive extruder

Possibility to recycle materials
Automatic pellet feeder **

Consult new products **

DESIGNED AND ASSEMBLED BY
INDART 3D

Teléfono: +34 943 943 855

e-mail: info@indart3d.com